



SS304 POZI RECESS CSK HEAD SCREW

Special Features

- Ideal furniture fastener, providing high pull out resistance.
- Can be reused.
- Manufactured to international specifications and standards.
- Choice of diameters and lengths ensure proper selection for application.
- Material: SS304.



Specifications

Item	Code Nos.	Size in mm	Finish
SS304 Pozi Recess CSK Head Screws	CBS 3016 SS	3 x 16 (5 x 16)	RS
	CBS 3516 SS	3.5 x 16 (6 x 16)	
	CBS 3520 SS	3.5 x 20 (6 x 20)	
	CBS 4025 SS	4 X 25 (8 x 25)	
	CBS 4035 SS	4 x 35 (8 x 35)	
	CBS 4050 SS	4 x 50 (8 x 50)	

Code Nos.	Size		d1	d2	D	P	a	b	r	L
CBS 3016 SS	3.0 x 16	Min.	2.80	1.50	5.70	1.35	1.60	1.90	1.20	15.1
		Max.	3.00	1.90	6.00				1.60	16.9
CBS 3516 SS	3.5 x 16	Min.	3.30	1.75	6.64	1.60	1.80	2.10	1.50	15.1
		Max.	3.50	2.15	7.00				1.90	16.9
CBS 3520 SS	3.5 x 20	Min.	3.30	1.75	6.64	1.60	1.80	2.10	1.50	19.0
		Max.	3.50	2.15	7.00				1.90	21.0
CBS 4025 SS	4.0 x 25	Min.	3.75	2.02	7.64	1.80	2.00	2.50	1.60	24.0
		Max.	4.00	2.50	8.00				2.10	26.0
CBS 4035 SS	4.0 x 35	Min.	3.75	2.02	7.64	1.80	2.00	2.50	1.60	34.0
		Max.	4.00	2.50	8.00				2.10	36.0
CBS 4050 SS	4.0 x 50	Min.	3.75	2.02	7.64	1.80	2.00	2.50	1.60	48.75
		Max.	4.00	2.50	8.00				2.10	51.25

		Recess No.	1 (for Ø3mm)	2 (for Ø3.5mm)	2 (for Ø4mm)		
Pozi Drive	m	Approx.	3.00	4.00	4.40	Material	SS 304
	n	Min.	1.60	1.76	2.05	Finish	Raw Stainless Steel
		Max.	2.01	2.06	2.51		

